

MRI Gastric Images Processing using a Multiobjective Fly Algorithm

Al-Maliki, Shatha; Lutton, Evelyne; Boue, Francois; Vidal, Franck

Published: 08/09/2018

Peer reviewed version

[Cyswllt i'r cyhoeddiad / Link to publication](#)

Dyfyniad o'r fersiwn a gyhoeddwyd / Citation for published version (APA):

Al-Maliki, S., Lutton, E., Boue, F., & Vidal, F. (2018). *MRI Gastric Images Processing using a Multiobjective Fly Algorithm*. Paper presented at Evolutionary Machine Learning, Coimbra, Portugal.

Hawliau Cyffredinol / General rights

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

- Users may download and print one copy of any publication from the public portal for the purpose of private study or research.
- You may not further distribute the material or use it for any profit-making activity or commercial gain
- You may freely distribute the URL identifying the publication in the public portal ?

Take down policy

If you believe that this document breaches copyright please contact us providing details, and we will remove access to the work immediately and investigate your claim.

MRI Gastric Images Processing using a Multiobjective Fly Algorithm ^{*}

S. Al-Maliki^{1,2}, E. Lutton³, F. Boué^{3,4}, and F. Vidal²

¹ Basrh University, Iraq

² Bangor University, United Kingdom

³ INRA-AgroParisTech, France

⁴ LLB, CEA CNRS, France

Abstract. When dealing with rare and sparse data, like the ones collected during a long and expensive experimental process, machine learning is used in a different perspective. In this context, optimisation-based approaches combined with user visualisation and interactions are sometimes the best way to cope with modelling issues. We present here an example related to an experimental project aiming at understanding the kinetics of gastric emptying using MRI images of the stomach of healthy volunteers. We show how a cooperation/co-evolution algorithm, the “Fly Algorithm”, can be made multi-objective, and its output, a complex Pareto Front, analysed using interactive Information Visualisation (InfoVis) and clustering.

Keywords: Machine Learning · Cooperative-co-evolution · Multi-objective optimisation · Pareto Front analysis · Visualisation

1 Introduction

The work presented here is part of a large project focused on the understanding of the influence of food structure on digestion. Advanced imaging techniques allow observing the digestion process at different scales. Small scale measurements were performed *in vitro* on large facilities (small-angle neutron scattering (SANS), small-angle X-ray scattering (SAXS), and X-ray imaging) [2,3] while magnetic resonance imaging (MRI) of the gastrointestinal tract (GIT) provides *in vivo* information at large scale (stomach and duodenum of healthy human volunteers).

We focus here on MRI observations of the kinetics of gastric emptying for two species of ingested food: i) progressively and partially digested cooked pasta, and ii) frozen garden peas, which keep their shape in early gastric stages (Fig. 1).

We show how a “Fly Algorithm” [4] can be efficiently adapted to detect peas in these MRI images (around 20 peas in one stomach for the current experimental data). Being able to follow peas in these images is important as it reveals how the food bolus is stirred inside the stomach to favour the action

^{*} The MRI data used in this study were collected at CEA-SHFJ with the support of IR4M CNRS/Orsay University (Xavier Maître and Luc Darrasse) in the framework of the IDI/Paris Saclay PhD of Daniela Freitas.

of the gastric juice. The Fly Algorithm has been turned into a multi-objective cooperative-coevolution algorithm, and expert knowledge has been integrated through simple Information Visualisation (InfoVis) techniques: a multi-objective scheme provides Pareto front data which needs to be understood and explored by the end-user.

2 The multi-objectives Fly Algorithm




Fig. 1. MRI slice of a human stomach containing peas and pasta.

Peas (not cooked nor chewed) keep their shape and size in early gastric stages. A pea thus appear in a MRI slices as a circle of a fixed radius of about 4mm ($R = 8$ pixels). It is darker and more homogeneous than the background. These properties are featured thanks to 7 objective functions. Objectives 1, 2 and 3 are based on homogeneity measurements (inside a circle or a ring centred on the potential pea position), while Objectives 4, 5, 6 measure the isotropy. Finally Objective 7 ensures the pea area is darker than its background.

The Fly Algorithm maintains a population of potential pea locations, and evolves it to optimise the previous 7 objectives using a multi-objective scheme (inspired from NSGA-II, [1]). The evolved population then stabilises on a Pareto front.

3 Visualisation and interactive decision making

Each point of the Pareto front not only corresponds to a possible pea location, but also to a different objective priority trade-off. Automatically extracting the points that really correspond to peas is not trivial. This can be done efficiently thanks to interactive visualisation.

A scatterplot displays the position of the individuals over the MRI image (see Fig. 2), while a parallel coordinates plot⁵ shows the values of the seven objective functions for each individual. The user can interactively select areas of points in the scatterplot that correspond to peas. Each selected area gets a unique colour, the same in both plots. 7 validity ranges (two thresholds per objective) are defined for filtering out the 25,000 individuals generated during the evolutionary process. The scatterplots are then clustered using a Gaussian Mixture Model (GMM) (see Fig. 3a). Clusters that are close to each other (e.g.

⁵ This plot represents a point in a n -dimensional space as a broken line with $n - 1$ segments, joining its n coordinates located on n vertical axes.




Fig. 2. Scatterplots and parallel coordinates plots of successive generations. All solutions (flies) are plotted in red by default. When the user selects an area in the scatterplot, a specific colour is assigned to this area and linked to the corresponding lines in the parallel coordinates plot.




Fig. 3. Candidate solution clusters.

within a pea diameter) are then merged. All clusters centres are extracted (see Fig. 3b). In total, 19 points were selected. Thanks to another parallel coordinates plot a new set of thresholds is defined (see Fig. 3c) to further refine the results and limit the number of false positive (i.e. points that do not actually correspond to peas). The last set of thresholds is used to highlight stronger candidates (7 purple dots in Fig. 4).

4 Conclusions and future work

We present here some preliminary results based on the first multi-objective version of the Fly Algorithm. We have also shown that an interactive process, combining image display, scatterplot and parallel coordinates plots, facilitates the analysis of the output of this Fly Algorithm.

This interactive scheme will be used to produce training data for a deep neural network, for a further robust and more automatic processing of the whole dataset (all MRI slices of 3D volumes and sequences of 3D volumes, at different digestion duration, for all volunteers). The next step will be to follow the peas as a set of particles, to reconstruct their movements inside stomach and their progressive ejection through the pylorus along digestion.




Fig. 4. Final result.

References

1. Deb, K., Pratap, A., Agarwal, S., Meyarivan, T.: A fast and elitist multi-objective genetic algorithm: NSGAII. *IEEE Transactions on Evolutionary Computation* **6**(2), 182–197 (Aug 2002). <https://doi.org/10.1109/4235.996017>
2. Floury, J., Bianchi, T., Thévenot, J., Dupont, D., Jamme, F., Lutton, E., Panouillé, M., Boué, F., Feunteun, S.L.: Exploring the breakdown of dairy protein gels during in vitro gastric digestion using time-lapse synchrotron deep-uv fluorescence microscopy. *Food Chemistry* **239**, 898–910 (2018). <https://doi.org/10.1016/j.foodchem.2017.07.023>
3. Lutton, E., Thevenot, J., Le Feunteun, S., Floury, J., Panouille, M., Dupont, D., Roblin, P., Boue, F.: Evolution of food gel structures during simulated gastro-intestinal digestion using small angle scattering at SOLEIL synchrotron. In: 5th International Conference on Food Digestion (2017), <https://prodinra.inra.fr/record/394314>
4. Vidal, F.P., Louchet, J., Lutton, E., Rocchisani, J.: PET reconstruction using a cooperative coevolution strategy in LOR space. In: *IEEE Nuclear Science Symposium Conference Record*. pp. 3363–3366. IEEE (Oct 2009). <https://doi.org/10.1109/NSSMIC.2009.5401758>